



Battle the Elements with Powder & Zinc

No other truck equipment manufacturer provides better environmentally friendly corrosion and abrasion protection than The Godwin Group.

| | Standard Liquid | Polyurethane | Powder Topcoat | Powder Topcoat with |
|-----------------------------|------------------|-----------------|-----------------|----------------------------|
| | Topcoat | system | only | Powder Zinc Primer |
| Corrosion Protection | | | Past Standard | New standard |
| - Salt Spray | 500 Hours | 2000 Hours 🐭 | 1000 Hours | 5000 Hours |
| - Humidity | 100 to 200 Hours | 1000 Hours | 800 Hours | 1000 Hours |
| Impact | 1 | 1 | | |
| - Forward | 50 lbs. | 80 lbs . | 80 lbs . | 80 lbs. |
| - Reverse | 30 lbs . | 80 lbs . | 80 lbs . | 80 lbs . |
| Pencil Hardness | HB-H | H-2H | H-2H | H-2H |
| - Gravel-o-meter (Chips) | 4 B | 5B | 5B | 5A No C size chips |

The Godwin Group sets the standard by which all other truck equipment manufacturers are measured. Thermoset Powder coating with thermoset Zinc primer is STANDARD equipment for Godwin, Williamsen, and Galion bodies. and Good Roads equipment. Zinc primer is standard on R/S equipment and available for an additional charge on Champion products.

Accelerated 5000 Hour Salt Spray Test with 5% Salt Solution. (Ocean water is 3%)



Powder Coated Only

Powder Coated with Zinc Primer

